

CHILLED SNACKS & COMBO VENDORS

VM Series



The features you want































- Adjustable inner temperature: min. +3°C in a room temperature of +32°C.
- Can be configured as single temperature Chilled Snack or with dual zones for Drink and Snack Combo.
- Shelves: made of galvanized steel and pre-coated.
- Adjustable height shelf system with increments every 16mm
- Anti-theft device fitted on the delivery door.
- Product sensor delivery system ensures vend success every time and satisfied customers.
- Large double glazed safety glass filled with Argon Gas to improve insulation and reduce fogging.
- Adjustable anti slip feet.
- Coin insertion slot forces single coin insertion and reduces coin jams.
- Quality stainless steel key gives trouble-free operation.
- Liquid Crystal Display and auto self diagnostic control system.
- Integral mains safety circuit breaker.
- Refrigeration unit R134a, easy removed for servicing.
- Removable metal plate for installation of cashless payment systems or bill validators.
- Conforms to CE marking requirement.
- Option of electronic health control to prevent sales on the predefined trays if temperature exceeds the pre-set value.
- Maintain temperature uniform between 10°C and 14°C with dual zone; between 3°C and 8°C in the lower 3 trays; between 14°C and 25°C in the upper 3 trays.
- Great product lighting and display with energy efficient LED lighting.

Electronic Features

Advanced electronics include:









































- Electronic multiple pricing.
- Full unit and value line by line sales audit.
- 24v DC Motors.
- MDB protocol for easy compatibility with electronic coin, note and cashless payment systems.
- Mechanisms and cashless systems.
- Electronic temperature control system.

VM3 Standard Configuration

Chips						
Chips						
Chocolate						
Bottles						
Cans						
Cans						





















































VM4 Standard Configuration

Chips								
Chips								
Chocolate								
Bottles								
Cans								
Cans								



VM5 Standard Configuration

Chips										
Chips										
Chocolate										
Bottles										
Cans										
Cans										



Standard Setup											
Model	Total Selections	Snack	Drink/ Capacity(cans)	Protocol	Change Giver	Bill Validator	Hight (mm)	Width (mm)	Depth (mm)	Weight (kg)	
VM3	30	12	18/108	MDB	Yes	Optional	1840	770	830	285	
VM4	40	16	24/144	MDB	Yes	Optional	1840	900	830	315	
VM5	50	18	30/180	MDB	Yes	Optional	1840	1060	830	340	



Australian Exclusive VM Series Equipment Importer
Unit 2, 24 Prince William Drive
Seven Hills NSW Australia 2147
PHONE: 1300 308 363
EMAIL: sales@autovending.com.au
www.autovending.com.au