

CV3 PLUS COMBO AND CHILLED SNACK

- ✓ Compact
- ✓ 90° Door Opening
- ✓ Assured Vend
- ✓ Heated Glass
- ✓ Ideal For Operators



Best In Class Features

Innovative Features

- ✓ Vend sensor in the delivery box guarantee product delivery
- ✓ Zinc alloy keyboard
- ✓ Coin insert slot (easy to use)
- ✓ Secure door with wraparound anti-vandal enclosures
- ✓ Beautiful glass door
- ✓ Anti-theft device installed in the delivery box
- ✓ Glass heater to avoid condensation
- ✓ Backlit stainless steel keypad
- ✓ Can be hooked up to a locker

Energy Efficiency

- ✓ Fully insulated foaming cabinet
- ✓ Double glazed viewing window with argon gas interspaces
- ✓ Led lighting to enhance product presentation & reduce energy costs

Cooling

- ✓ Refrigerator with r-134a, complies with international standards
- ✓ Excellent cooling unit with Embraco compressor
- ✓ Dual temperature zones for drink and snack
- ✓ Preserving temperature:
 - between 4°C and 10°C in the lower 3 trays
 - between 14°C and 25°C in the upper 3 trays

Shelving

- ✓ Adjustable shelf height every 15mm
- ✓ Snack shelves tilt down 25° for easy loading
- ✓ Dual or single spirals for different sized products
- ✓ 360° helix adjustability in 20° increments provides flexibility to vend virtually anything

Payment Systems

Advanced electronics include:

- ✓ MDB protocol support for all industry standard devices including cash, coin, debit and credit systems
- ✓ DEX and cashless payment system enabled to allow online remote monitoring

Additional Options

- ✓ Optional 7" LCD screen
- ✓ High capacity can tray holds up to 54 12oz (330ml) cans
- ✓ Interior manual case
- ✓ Optional slave machine. Easy to be installed with master machine



CV3 PLUS Standard Configuration

Chips	8	8	8		
Chips	8	8	8		
Chocolate	12	12	12	14	14
Bottles	5	5	5	5	5
Cans	6	6	6	6	6
Cans	6	6	6	6	6

Simple yet full-featured interfaces

- ✓ Programmable LCD display
- ✓ Standard peripheral opening for additional payment or POS systems
- ✓ MDB support for all industry standard devices including cash, coin, debit and credit systems
- ✓ DEX data output support

Model	CV3 PLUS							
Width (mm)	Height (mm)	Depth (mm)	Weight (kg)	Change Giver	Bill Validator	Protocol	Power Consumption	Power Supply
777	1830	820	225 - 245	YES	YES	MDB	490W	AC 220V ~240V 50HZ